


NEUROS & IMMUNOS

Neuros & Immunos offers an avenue of amenities such as cafeterias and gym amidst the organic presence of lush landscape. It is an ideal break-away destination that facilitates tenants' discussion and interactions. Neuros 8 Biomedical Grove Singapore 138665

Immunos 8A Biomedical Grove Singapore 138648





LOCATION

- Neuros: 8 Biomedical Grove Singapore 138665
- Immunos: 8A Biomedical Grove Singapore 138648

ACCESSIBILITY

- Within 5 minutes' drive from National University of Singapore, National University Hospital and Singapore Science Park
- 15 minutes' drive from Central Business District
- Within walking distance to Buona Vista MRT station
- Shuttle bus services to Buona Vista MRT station provided by JTC

BUILDING SPECIFICATIONS

Type of Building

- 7-storey R&D building with retail spaces at its first storey
- BCA Green Mark Gold Award
- Green features: Motion-sensor lightings, toilets with water-saving fittings and recycling corner

Floor Area

• Total NLA: Approx. 28,292 sqm

Unit Sizes

- Retail: Approx. 30 sqm 180 sqm
- Research lab/office: 110 sqm 530 sqm (2nd storey)
- Research lab: 170 sqm 700 sqm (3rd to 7th storey)

Floor Loading

- 1st storey: 5.0 kN/sqm
- 2nd 6th storey: 7.5 kN/sqm
 7th storey roof: 12.5 kN/sqr
- 7th storey roof: 12.5 kN/sqm

Ceiling Height

- Floor to floor
 1st storey: 4.1 m 6.7 m
 - 2nd 5th storey: 5.2 m
 - 6th 7th storey: 7.5 m

Column Grid

• Approx. 13.3 m x 14.3 m

Lifts

- Passenger lifts: 5 x 1,350 kg (20 persons) (2 x Neuros and 3 x Immunos)
- Service lift: 1 x 2,500 kg at each block
 - Dimension: 2.45 m (W) x 1.9 m (D) x 2.8 m (H)
 - Lift car door size: 2.45 m (W) x 2.8 m (H)
- Car park lift: 1 x 900 kg (13 persons) at each block

Loading Bay Facilities

- Immunos level 1 2 loading/unloading bay with dock leveller
- Neuros & Immunos B1 3 loading/unloading bays with dock leveller

Parking Lots

- Car: Approx. 286
- Parking lot allocation: 1 lot per 200 sqm leased

Dedicated Lab-Friendly Features

- District cooling system
- Modular, column-free units of 13.3 m by 14.3 m enables flexible lab and benching configurations for different tenant's needs
- Centralised cores that serve outward facing lab facilities
- Insulated light-weight fire-rated partition dry wall with raw concrete floor finish
- Windows with low E vision glass panels

Power Supply Allocation


- Research lab/office units: 236 VA or 0.34 amps per sqm of lettable area
- Retail units: 200 VA or 0.29 amps per sqm of lettable area

Provisions

- Telecommunication facilities: Tap-off points available at the TAS riser ducts
- MATV connection: Tap-off points available from riser ducts

Amenities

• Cafe, clinic and fitness centre



Disclaimer

The Developer makes no representations or warranties, conditions, undertakings or terms either expressed or implied as to the condition, quality, accuracy, fitness for purpose, completeness of the information contained herein or that such information will be accurate, up to date, or free from error. All art renderings and pictures herein are artist's impressions only and all specifications stated herein are subject to re-survey and approval from the relevant authorities. The information and specifications contained herein do not form part of an offer or a contract and neither the Developer nor their appointed Marketing Agents can be held for any inaccuracies, changes, losses or dramate article theoreticm.